

Connector

Type
PV-LR5




Technical data

Rated Current	40A/50A(IEC), 30A/40A(UL)
Rated Voltage	1500V(IEC) / 1500V(UL)
Cable Type	4mm ² / 6mm ²
OD of Suitable Cables	Type I $\phi 5.6\text{mm} < \text{OD} \leq \phi 6.6\text{mm}$
	Type II $\phi 6.6\text{mm} < \text{OD} \leq \phi 7.2\text{mm}$
	Type III $\phi 4.5\text{mm} \leq \text{OD} \leq \phi 5.6\text{mm}$
Degree of Protection, mated	IP68(1.2m, 1h)
Degree of Protection, unmated	IP2X
Ambient Temperature Range	-40°C~+85°C
Safety Class	II

Remark: Type I connectors are used for standard product, contact LONGi Customer Service in case for special requirements.

Complete System and Product Certifications

IEC 62852 (ed.1) , EN 62852: 2015
ISO 9001: 2015 ISO Quality Management System
ISO 14001: 2015 ISO Environment Management System
ISO 45001: 2018 ISO Occupational Health and Safety
IEC 62941 Guideline for module design qualification and type approval



No. 8369 Shang Yuan Road, Economic And
Technological Development Zone, Xi'an, China
Tel: +86-21-80162606
www.longi.com

LONGi has the sole right to make
such modification at anytime
without further notice.
(20230504 V3.0)